

Surfaces creating inspiration.



StyleLite Acrylic

Specifications 2023

A superior range of gloss and matte panels for interior cabinetry. Crafted using TruColor, a multilayer UV barrier technology, StyleLite Acrylic is the perfect material to create luxury kitchen and bathroom cabinetry, bespoke furniture, and feature panels. The laminate is made in Australia and pressed to the board in our NZ factory to order.

StyleLite Acrylic is available in a range of coextruded solid colours with matching edging available.

A range of
colours/surfaces

Stocked

Matching
Edging

1 week
Production lead
time

Features:

- High scratch and abrasion resistant
- Very high UV resistant
- Consistent finish
- Allows fabricator to create a near seamless edge
- Consistent thickness
- Easy clean surface
- Water and moisture resistant
- High anti-fingerprint resistant (Matt)
- Recyclable



Perfect for

Kitchen Cabinetry | Bathroom Cabinetry | Laundry Cabinetry | Retail Display
Office Furniture & Partitions | Motorhome & Caravan Interiors



10 Year
Manufacturer's
Guarantee



Free
samples on
all products



Manufactured
right here in
New Zealand



Prefabricated
and ready for final
application



Manufactured
using FSC
certified MDF

How to Specify

1. Select a finish from the product catalogue or at Compac Panels website.
2. Establish the date the joiner or builder will require the panel/s.
3. Consider the product lead time.
4. To order, contact panels@compacgroup.co.nz to confirm the project and approximate timeline, naming the substrate, colour and quantity required.

Thickness and Substrate

- Stocked as pressed to 16mm MR-MDF sheet size (2440x 1220)
- Other thicknesses and substrates available on request

Restrictions:

- May not be used as structural elements in walls and ceilings
- Final application must be in interior conditions
- Must not be exposed to excess moisture or humidity

Sustainability

StyleLite Acrylic panels are made using an MDF substrate sourced from sustainable forests and processed by fully qualified FSC and PEFC mills in New Zealand. NZ-made MDF meets Environmental Choice standards for formaldehyde emission levels of $E0 \leq 0.5\text{mg/L}$, which makes it safe to work with. All StyleLite Acrylic laminates are made using sustainably sourced wood fibres and other environmentally safe products. This ensures what Compac Panels supplies to the market reflects the values we carry as environmentally responsible New Zealanders.

Compliance

All panels by Compac Panels are manufactured using E0 $\leq 0.5\text{mg/L}$ substrate, to meet FSC formaldehyde emissions standards for NZ. MDF substrate has been tested to New Zealand Building Code Verification NZBC C/VM2 Fire Classification Group Number 3. HPL laminate is BS EN 438-3 approved, which is a universally recognised standard for laminates that are $< 2\text{mm}$ thick and intended for bonding to a foundation substrate. All panels must be used in accordance with the NZ Building Code.

StyleLite Acrylic Storage and Care Guide

(This guide should be read in conjunction with the StyleLite Acrylic warranty.)

Employ best handling practices when moving panels due to their size/weight. Store panels in dry, well-ventilated conditions, placed horizontally on a flat surface. Avoid over-stacking and keep away from flames or excess heat. Do not store panels in an upright position as this may cause warping.

While our panels are water resistant, they aren't completely waterproof. Care should be taken to ensure to avoid excessive exposure to water, steam, or extreme humidity. Care should also be taken to protect panels from high temperatures caused by steam or heat leaks.

Clean panels with a warm damp cloth (microfibre is ideal), with all excess water removed. Wipe away any remaining moisture with a dry cloth. Alternatively, use a dry cloth with a streak-free glass cleaner or standard household surface cleaning spray. For more difficult stains, try dishwashing detergent on a damp cloth.

Never use the following products on StyleLite Acrylic panels, as these will damage the surface:

- Abrasive cleaners
- Bleach such as Janola or similar
- Scouring pads, wire wool, sandpaper
- Solvents and thinners.

Use of any chemical substances, solvents, and abrasive substances on panel surfaces will void the warranty.