

Surfaces creating inspiration.



IndoPly

Specifications

INDO Ply is Imported by CompacPanels as sustainably grown high, quality light plywood with a mixed Harwood surface. The plywood origin is Indonesia and produced using high quality equipment in a controlled envroment. Each batch is quality checked before been packed into containers and sent to New Zealand.

Light
Weight

Range of
Thicknesses

Stocked

High-quality
mixed hardwood surface

Features:

- Light weight Falcatta Core
- Mixed hardwood face
- BB / BB faces
- Stable and constant
- Sheet Size – 2440 x 1220mm.



Perfect for

Auto Motive fit outs | Laminating | General Joinery | Furniture | Shop Fittings | Shopfittings |
Excellent surface for lacquering



10 Year
Manufacturer's
Guarantee



Free
samples on
all products



Manufactured
right here in
New Zealand



Prefabricated
and ready for final
application



Manufactured
using FSC
certified MDF

How to Specify

1. Select a finish from the product catalogue or at Compac Panels website.
2. Establish the date the joiner or builder will require the panel/s.
3. Consider the product lead time.
4. To order, contact panels@compacgroup.co.nz to confirm the project and approximate timeline, naming the substrate, colour and quantity required.

Thickness and Weights

Sheet Thickness (mm)	Sheet Weight (KG)
3	3.5
9	10.5
12	14
15	17.4
18	21

Restrictions:

- May not be used as structural elements in walls and ceilings
- Final application must be in interior conditions
- Must not be exposed to excess moisture or humidity

Sustainability

INDO Ply complies with **INDONESIAN LEGAL WOOD**, which is a Timber Legality assurance system (SVLK)
For processing INDO PLY it is important to utilise the required PPE and machinery with dust extraction.

Compliance

INDO Ply is manufactured in Indonesia from plantation forests. All the trees are often grown on farms and mature in about 9 years. This makes the wood light weight and perfect for plywood production and has been sustainable. CompacPanels takes extra diligent steps to partner with suppliers that share and display the same environmental values.

IndoPly Storage and Care Guide

(This guide should be read in conjunction with the IndoPly warranty)

Employ best handling practices when moving panels due to their size/weight. Store panels in dry, well-ventilated conditions, placed horizontally on a flat surface. Avoid over-stacking and keep away from flames or excess heat. Do not store panels in an upright position as this may cause warping.

While our panels are water resistant, they aren't completely waterproof. Care should be taken to ensure to avoid excessive exposure to water, steam, or extreme humidity. Care should also be taken to protect panels from high temperatures caused by steam or heat leaks.